

General Purpose Hose

Our General Purpose Hose is a premium 300 psi high oil resistant non-conductive push-on hose that will provide smooth, safe performance in oily and harsh conditions.

NOTE: Not recommended for unleaded gasoline.



Cover Color: Black

Oil Resistance: High

Construction:

Tube: Nitrile, RMA Class A

Cover: Nitrile/PVC RMA Class A

Reinforcement: Spiral polyester

Temperature Range:

-30°F to +180°F

-34°C to +82°C

Resistance



Branding

Non-Conductive Size 300 PSI WP
Made in USA MSHA 1C

Part #	Stk. Code	Reel Size	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
			(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
761-4	27004	250'	1/4	6.35	0.50	12.70	2	300	2.07	1.50	38.10	0.10	0.15
761-6	27006	250'	3/8	9.53	0.63	15.88	2	300	2.07	2.25	57.15	0.13	0.19
761-8	27008	250'	1/2	12.70	0.75	19.05	2	300	2.07	3.00	76.20	0.16	0.24
761-10	27002	250'	5/8	15.88	0.91	23.02	2	300	2.07	3.75	95.25	0.23	0.34

2345 Walden Ave. Suite 100
Cheektowaga, NY 14225
P. 1.800.776.5549
F. 716.894.9623
E. orders@tectran.com

2400 Anson Dr.
Mississauga, ON L5S 1G2
P. 905.678.7700
F. 905.678.6210
E. customerservice@tectran.com